

## Standard Sausage Pillowcase

### Material List:

Body of Pillowcase	$\frac{3}{4}$ Yard (27") Fabric
Header of Pillowcase	$\frac{1}{4}$ Yard (9") Fabric
Piping/Trim is optional	1-1/2" to 3" of contrasting fabric (fold in $\frac{1}{2}$ , wrong sides together & press)

### Instructions:

1. Lay  $\frac{1}{4}$  yard (Width of Fabric) **right side up** (9" Header)
2. Place  $\frac{3}{4}$  yard (WOF) **right side up** (27" Body) on top of the header. (Matching the top raw edges)
3. Optional: Place piping or trim, matching raw edges to the top of the first two pieces. Pin in place to avoid slipping. Large Rick Rack or 2-1/2 to 3" folded in half works great.
4. Roll or fold up the  $\frac{3}{4}$  yards of fabric of the body until you seen the bottom  $\frac{1}{4}$  yard. Keeping raw edges together, re pin the  $\frac{1}{4}$  yard over the rolled fabric. (the trim and body pieces are now inside this tube.
5. Sew your  $\frac{1}{2}$ " seam across the top; then pull the fabric out of your tube.
6. Press the header of the pillowcase.
7. Iron with wrong sides together. Sew a scant  $\frac{1}{8}$ " down the side and bottom of pillow case.
8. Trim close to sew line, invert pillowcase and sew  $\frac{1}{4}$ " down side and bottom. This is a French Seam, so you have no raw edges showing.